

Vision™ OPLC™

Technical Specifications

Models V570-57-C30B, V570-57-T40B

This guide provides specifications for Unitronics' color touchscreen controllers V570-57-C30B and V570-57-T40B. You can find additional documentation on the Unitronics' Setup CD and in the Technical Library at www.unitronics.com.

Technical Specifications

Power Supply

Input voltage	24VDC
Permissible range	20.4 VDC to 28.8VDC with less than 10% ripple
Max. current consumption	320mA@24V
Typical power consumption	6.5W

Battery

Back-up	7 years typical at 25°C, battery back-up for RTC and system data, including variable data.
Replaceable	Yes, without opening the controller.

Graphic Display Screen

LCD Type	V570-57-C30B	V570-57-T40B
	CSTN	TFT
Illumination backlight	CCFL fluorescent lamp	
Display resolution, pixels	320x240 (QVGA)	
Viewing area	5.7"	
Colors	256	
Touchscreen	Resistive, analog	
'Touch' indication	Via buzzer	
Screen contrast	Via software (Store value to SI 7). See Note 1.	
Screen brightness	Via software (Store value to SI 9).	
Keypad	Displays virtual keyboard when the application requires data entry.	

Notes:

1. CSTN screens support both contrast and brightness. TFT screens support brightness only.

Program

Application memory	2MB		
Operand type	Quantity	Symbol	Value
Memory Bits	8192	MB	Bit (coil)
Memory Integers	4096	MI	16-bit
Long Integers	512	ML	32-bit
Double Word	256	DW	32-bit unsigned
Memory Floats	64	MF	32-bit
Timers	384	T	32-bit
Counters	32	C	16-bit
Data Tables	120K (dynamic)/ 192K (static)		
HMI displays	Up to 1024		
Program scan time	9 µsec per 1K of typical application		

Dimensions

Size	197X146.6X68.5mm (7.75" X 5.77" X2.7")
Weight	750 gm (26.4 oz)

Mounting

Panel-mounting	Via brackets
----------------	--------------

Environment

Inside cabinet	IP20 / NEMA1 (case)
Panel mounted	IP65 / NEMA4X (front panel)
Operational temperature	0 to 50°C (32 to 122°F)
Storage temperature	-20 to 60°C (-4 to 140°F)
Relative Humidity (RH)	5% to 95% (non-condensing)

The information in this document reflects products at the date of printing. Unitronics reserves the right, subject to all applicable laws, at any time, at its sole discretion, and without notice, to discontinue or change the features, designs, materials and other specifications of its products, and to either permanently or temporarily withdraw any of the forgoing from the market.

All information in this document is provided "as is" without warranty of any kind, either expressed or implied, including but not limited to any implied warranties of merchantability, fitness for a particular purpose, or non-infringement. Unitronics assumes no responsibility for errors or omissions in the information presented in this document. In no event shall Unitronics be liable for any special, incidental, indirect or consequential damages of any kind, or any damages whatsoever arising out of or in connection with the use or performance of this information.

The tradenames, trademarks, logos and service marks presented in this document, including their design, are the property of Unitronics (1989) (R"G) Ltd. or other third parties and you are not permitted to use them without the prior written consent of Unitronics or such third party as may own them.